

# GK-832-21

## Circular Twin LNBF

- High Gain LNBF
- Easy Installation (40mm)
- Excellent Performance
- Low Power Consumption
- 100% Water Leak Proof



**RoHS**  
COMPLIANT

SPECIFICATION	
INPUT FREQUENCY RANGE	11.7~12.75 GHz
REFLECTOR TYPE	OFFSET
F/D RATIO	0.5~0.7
CROSS POL. ISOLATION	20 dB (typical)
NOISE FIGURE	0.6 dB (typical)
CONVERSION GAIN	62 dB (typical)
GAIN FLATNESS	±0.5 dB / 27 MHz
OUTPUT FREQUENCY	950 ~ 2000 MHz
L.O. FREQUENCY	10.75 GHz
L.O. PHASE NOISE	-55 dBc / Hz ( @ 1KHz ) -80 dBc / Hz ( @ 10KHz ) -100 dBc / Hz ( @ 100KHz )
OUTPUT POWER LEVEL (AT 1 dB GAIN COMPRESSION)	0 dBm
IMAGE REJECTION	40 dB (min.)
OUTPUT VSWR	2.5 : 1 (MAX.)
OUTPUT CONNECTOR	75 Ω F TYPE FEMALE
DC CURRENT CONSUMPTION	180 mA
OPERATING VOLTAGE	(1) 11.5 ~ 14.0 V → R.H CIRCULAR POLARIZATION (2) 16.0 ~ 19.0 V → L.H CIRCULAR POLARIZATION
OPERATING TEMPERATURE	-40°C ~ +60°C



**FULLWAY COMMUNICATIONS LTD.**

No. 18, Alley 20, Lane 835, Sec.1, Zhonghua Rd. Zhongli Dist,  
Taoyuan City320, Taiwan  
Tel: 886-3-461-1138 Fax: 886-3-461-7290

Email: [sales@fullway.com.tw](mailto:sales@fullway.com.tw)

Website: [www.fullway.com.tw](http://www.fullway.com.tw)